



DECLARATION OF CONFORMITY

DATE OF ISSUE: 2025-05-22

VALID TO: 2027-05-22

Product: CAKE PLATE GOLD/SILVER AND GOLD/BLACK

According to the information given by our raw material suppliers, we confirm that the raw materials used in the product fulfil the requirements and recommendations on packaging materials used for articles or components of articles intended to come in to contact with food according to:

Solid board laminated 2 sides metalized PET foil gold/silver

- Regulation (EC) No 1935/2004 on material and articles intended to come in contact with food
- Regulation (EC) No 2023/2006 with amendments on good manufacturing practice for material and articles intended to come in contact with food
- (EU) No 10/2011, which deals with products and materials that are intended to come into contact with food.
- BFR recommendation XXXVI, paper and board, with limitations mentioned in Instructions for safe and appropriate use.

- The PET foil is a functional barrier for the conditions of intended use as per the results of the migration tests performed according to regulation (EU) No 10/2011 on plastic materials and articles intended to come into contact with food.

• **Dual use substances (in foil)**

| FMC substance No | CAS no | Substance name | SML (mg/kg) |
|------------------|-----------|-----------------|-------------|
| 509 | 7664-38-2 | Phosphoric acid | - |
| 504 | 7631-86-9 | Silicon dioxide | - |



DECLARATION OF CONFORMITY

DATE OF ISSUE: 2025-05-22

VALID TO: 2027-05-22

Overall migration tests*

| Conditions | Simulant | Measured Value |
|-----------------|----------------|------------------------|
| 10 days at 40°C | 3% acetic acid | < 2 mg/dm ² |
| 2 days at 20°C | Isooctane | < 2 mg/dm ² |
| 10 days at 40°C | 95% ethanol | < 2 mg/dm ² |
| 10 days at 40°C | 50% ethanol | < 2 mg/dm ² |

Ratio of food contact surface area to volume: 2 dm²/100 ml

Specific migration tests*

| Parameter | Conditions | Simulant | Measured Value | SML Value |
|---|-----------------|----------------|----------------|--------------|
| Di-/Monoethylene glucol | 10 days at 40°C | 95% ethanol | < 10 mg/kg | 30 mg/kg |
| Isophthalic acid | 10 days at 40°C | 3% acetic acid | < 0,5 mg/kg | 5 mg/kg |
| Perfluorooctanoic acid | 2 hr at 60 °C | 95% ethanol | < 0,05 µg/kg | 0,05 µg/kg |
| Terephthalic acid | 10 days at 40°C | 3% acetic acid | < 0,5 mg/kg | 7,5 mg/kg |
| Bisphenol-A | 10 days at 40°C | 95% ethanol | < 0,01 mg/kg | 0,05 mg/kg |
| Benzylbutylphthalate, BBP | 2 days at 20 °C | isooctane | < 1 mg/kg | < 3 mg/kg |
| Bis-(2 ethylhexyl)phthalate, DEHP | 2 days at 20 °C | isooctane | < 0,1 mg/kg | < 0,3 mg/kg |
| Sum of Diisobutylphthalate (DIBP), Dibutylphthalate (DBP) | 2 days at 20 °C | isooctane | < 0,01 mg/kg | < 0,01 mg/kg |
| Sum of Diisononylphthalate (DINP), Diisodecylphthalate (DIDP) | 2 days at 20 °C | isooctane | < 0,5 mg/kg | < 0,5 mg/kg |

ARISTO AB
Truckgatan 26
442 40 KUNGÄLV
SWEDEN

Phone: +46(0)303-24 61 00

E-mail: aristo@aristo.se
Homepage: www.aristo.se



DECLARATION OF CONFORMITY

DATE OF ISSUE: 2025-05-22

VALID TO: 2027-05-22

- Following substances are not intentionally added in the production of board
Phthalates, Bisphenol A, PFAS, PFOA, Formaldehyde, GMO

- Packaging and Packaging Waste Directive

The paperboard complies with Packaging and Packaging Waste directive 94/62EC amended by Directive 2018/852/EC and Regulation 2009/219EC.

REACH

All paperboard is defined in Article 3 of the REACH Regulation.

Intended use

The paperboard may stand in direct contact with wet and/or fatty foodstuffs and dry, non-fatty foodstuffs

Duration and temperature of treatment and storage Any long-term storage at room temperature or below, including when packaged under hot-fill conditions, and/or heating up to a temperature T where $70\text{ °C} \leq T \leq 100\text{ °C}$ for a maximum of $t = 120/2^{((T-70)/10)}$ minutes .

Disclaimer

The declaration of conformity presupposes that the packing material is processed Properly. The assessment of the suitability of packaging material for the intended application is the responsibility of the user.

Possible interactions of packaging material and its components with product are to check according to end use of food packer

KUNGÄLV 2025-05-22